

System Specification

Item	Specification
Number of rack connection	2 connection,3 connection(selectable) ※Even number recommended
Number of steps・Size・Height	Number of steps, size, height can be selectable
Load capacity(for 1step)	500kg,1000kg,1500kg,2000kg can be selectable
Size of control panel	H1600 × W800 × D250 ※Separate placement is possible
Running speed	Max.0.6km/h(10m/min) Regular use 0.3km/h(5m/min)
Power source voltage	200V 50/60Hz
Fall prevention measure	Fall prevention rails installation on upper racks
Safety measure	Immediate stop when approaching area sensor, availability of operation by safety key ※Depending on your request, addition is available
Warning light・Alarm	Activated by each operation ※Depending on your request, addition is available
Operation procedure	Bulk operation by touch panel ※Remote operation by tablet is available (option)
System	Storage information registration, Auto moving of running rack when receiving and shipping

Inventory management

- 1 Entering product information, changeable for selected items by your request.
- 2 Possible to take the product information by barcode ,QR code and IC tag.
- 3 Product information and empty space can be confirmed immediately by touch-panel.
- 4 When storage and retrieval ,racks will be moved depending on the selected position.
- 5 The old product will be selected automatically if there are several same selected products.



Incoming Inventory List Screen



Product Inventory Screen



Outcoming Inventory List Screen



Distinctive technology and high-quality product !

TECHNO ROLL CO.,LTD.

Head Office 3-4-5,Techno-Stage,Izumi,Osaka,594-1144 Japan
Factories: TEL 81-725-53-3933 FAX 81-725-53-3922
Kanto Branch: 124-1,Hukuda,Kawagoe,Saitama,330-0821 Japan
TEL 81-49-299-5000 FAX 81-48-299-5671

URL: <http://www.technoroll.co.jp>

E-mail: info@technoroll.co.jp



HP



登録証番号:JQA-EM5066
本社・工場 / 関東支店
TEC-TARS-2404-E